For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

V1-**KC Speedi Plumb® Vinyl Faucet Connectors - Compression Inlet x KC Nosepiece Outlet

Use: For use in potable water distribution systems in accessible locations only

Design Features:

- No kink hose. The specially engineered reinforced PVC hose provides unique flexibility to prevent kinking and crimping
- Strong & durable with a tighter weave and two-layer bonded construction, outperforms conventional vinyl connectors
- Longer wing nuts ease installation for speedier connections
- Rubber washers provide a large pliable sealing surface and ensures a long lasting water tight connection
- 8-sided pneumatic crimp provides greater dependability for reliable nut-to-hose connections



Operating Specifications:

Temperature: 40°-160° F, intermittent to 180° F


Pressure: 125 PSI maximum

Tubing Diameter: 0.300" ID (0.500" OD)




CONNECTOR MATERIAL SPECIFICATIONS		
Hose	PVC with polyester braid reinforcement	
Barb	Brass	
Ferrule	Steel, zinc plated	
Nut	Brass, plated	
Washer	Rubber	
Compression Nut	Brass, plated	
Compression Ring	Brass	

	V1-12KC F	3/8" compression x 3/8" compression x 12" lengt
	V1-20KC F	3/8" compression x 3/8" compression x 20" lengt



V1-**KC Speedi Plumb® Vinyl Faucet Connectors - Compression Inlet x KC Nosepiece Outlet



PART DIMENSIONS (Inches)		
Model	DIM. A	
V1-12KC	12.0 / 13.0	
V1-20KC	20.0 / 21.0	

Listings & Certifications:

 IAPMO listed to ASME A112.18.6 and CSA B125.6 (includes NSF/ANSI372 and NSF61)





