



60" [1524mm] Bathtub w/ 18" [457mm] Threshold  
& 4 or 6 Jet Whirlpool Package

Left Hand Version (4630L:4 or 4630L:6) Shown

#### PRODUCT SPECIFICATIONS:

- \* Certified to meet CSA B45.5/IAPMO Z124 Standard.
- \* Product has a Class B fire rating as determined by ASTM E-84 test method.
- \* When installing this whirlpool, an access area should be provided near the location of the whirlpool pump for future access. An access area is required by many local, state & federal building codes.
- \* Recommended access area dimensions: W-20" [508mm] H-15" [381mm]
- \* Reinforced & slip resistant floor.
- \* Integral 1" [25mm] nailing flange.
- \* Factory drilled 2-1/2" overflow.
- \* Bathwell Dimensions (At Top): W-52-1/4" [1327mm] D-19" [483mm] H-15-1/2" [394mm]
- \* Bathwell Dimensions (At Bottom): W-44-1/2" [1130mm] D-17-1/2" [445mm]
- \* Bathwell Capacity (At Overflow): 42 gal. [159L]
- \* Water Level (At Overflow): 12" [305mm]
- \* Available without an overflow model becomes number (4630LM:4 or 4630LM:6 or 4630RM:4 or 4630RM:6)
- \* All dimensions +/- 1/2" [12.8mm]
- \* Clarion Bathware reserves the right to change design and/or dimensions.
- \* Dimensions are the same for all other versions of this model.

## 4630L:4 or 4630L:6 or 4630R:4 or 4630R:6

60" [1524mm] Bathtub w/ 18" [457mm] Apron, 4 & 6 Jet Whirlpool Package & Left or Right Hand Drain

**Clarion**  
BATHWARE  
44 Amsler Ave.  
Shippensburg, PA 16254

Phone: (814) 226-5374  
Toll Free: (800) 576-9228  
Fax: (814) 226-0730  
www.clarionbathware.com

Signatures For Approval:

Date:

Customer: \_\_\_\_\_  
Arch./Engr: \_\_\_\_\_

Quote #: \_\_\_\_\_  
Job Name: \_\_\_\_\_

DWG. #  
RE4630L or R -4&6  
JETCUT

By: NMH  
Date: 9/17/2021