



MAINLINE

Air Admittance Valve

Product Specifications

FEATURES

- Available in PVC or ABS
- One way valve to allow air in, to vent or equalize pressure in waste pipes.
- Rated up to 160 DFU
- 100% functionally tested



✓ To Submit	Part #	Description
	MLJBSP6T	6 DFU PVC Air Admittance Valve with 1-1/2" to 2" Threaded Adapter
	MLJBSA6T	6 DFU ABS Air Admittance Valve with 1-1/2" to 2" Threaded Adapter
	MLJBSPT300	20 DFU PVC Air Admittance Valve with 1-1/2" to 2" Threaded Adapter
	MLJB SAT500	20 DFU ABS Air Admittance Valve with 1-1/2" to 2" Threaded Adapter

SIZING CHART	
HORIZONTAL BRANCH SIZE	MAX DFU'S
1-1/2"	3
3"	20
4"	160

PERFORMANCE PARAMETERS	
Temperature Range	-20°C to +60°C (CE)
Open Pressure	-70 Pa -0.001PSI
Max. Pressure Rating Tightness	10,000 Pa (1m/40" H ₂ O) at 0Pa or higher

AIR FLOW CAPACITY		
Branch	6.85 l/s	1 to 160 DFU
Stack	6.85 l/s	8 to 24 DFU



Contact your sales representative for more information or visit our website at mainlinecollection.com