

SPEAKMAN® SM-3060

Versatile™ Pressure Balance Shower Package

FEATURES:

- Includes Sentinel Mark II® concealed anti-scald balanced pressure shower valve and handheld spray combination.
- Chrome plated brass wall plate with metal index.
- Chrome plated brass lever handle.
- Independent center sleeve allows up to 1 in. of rough-in variation.
- Adjustable temperature limit stop. Brass body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- Can be installed back-to-back.
- Roughing-in template.
- Four port valve with 1/2 in. female copper sweat inlets and shower outlet (tub outlet 1/2 NPT female).
- Furnished with 1/2 in. pipe plug.
- Chrome plated brass supply ell with wall flange.
- Chrome plated transfer valve with zinc lever handle and brass body
- S-2272-E2 showerhead with flow control device reduces flow to a maximum of 2.0 gpm (7.6 L/min)
- S-2500 shower arm and wall flange.
- In-line vacuum breaker.
- VS-100-PC handshower with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum.
- 69 in. square lock stainless steel hose with rubber liner.
- 42 in. slide bar with mounting screws. Swivel connector.



FINISH:



PC

COMPLIANCE:

- ASSE 1016 & ASME 112.18.1/CSA B125.1 standards (SM-3000 valve)
- WaterSense certified (S-2272-E2 shower head)

OPTIONS: Add suffix to model

- Integral stops -IS
- Less showerhead -LH
- 69 in. white vinyl hose -VH
- S-2251 showerhead -1
- S-2252 showerhead -2
- S-2253 showerhead -3
- S-2253-E15 showerhead -3E15
- S-2292 showerhead -9
- Contractor Packs Available

WARRANTY:

- 5 year limited

Architect/Engineer Approval Space:

SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: OCTOBER 2017

NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified all inlets and outlets are 1/2" female copper sweat. 3. The location of the wall posts(2) and supply ell are optional, but restricted by the 6'9" hose length running from the supply ell connection to hand shower and the 6" minimum requirement between the in-line vacuum breaker and top of the hand shower (hand shower adjusted to the highest position). 4. For ADA mounting locations consult ADAAG, ANSI A117.1 or state regulations.

DIMENSIONS:

