



SYMMONS® Visu-Temp®
the smart choice™

Comfort at a Glance

In one attractive unit the Symmons Visu-Temp® combines the controlled Pressure-Balancing of Safetymix with the visual control of a thermometer. Symmons Visu-Temp® lets you set the temperature you want, in degrees Fahrenheit or Celsius, just by turning the handle. "Average Shower Temperature 100° F / 38° C" is marked on the dial to eliminate guesswork.



Symmons Visu-Temp®
is available in
this finish:



Polished
Chrome



1-100VT

Visu-Temp Shower Unit, 4-500VT, 4-231 showerhead, 300 arm and flange.

4-500-VT Valve only



1-210VT

Visu-Temp Tub/Shower Unit, 4-500VT, 4-451 button diverter, 060 tub spout, 4-231 showerhead, 300 arm and flange.



1-25VT-FS

Visu-Temp Hand Spray Shower Unit, 4-500VT valve, FS hand spray.



1-50VT-FS

Visu-Temp Tub/Shower Unit with Hand Spray, 4-500VT, 4-45B lever diverter, FS hand spray, 060 tub spout.



1-117VT-FS

Visu-Temp Shower Unit with Hand Spray, 4-500VT, 4-45B lever diverter, FS hand spray, 4-231 showerhead, 300 arm and flange.



1-317VT-FS

Visu-Temp Tub/Shower Unit with Hand Spray, 4-500VT, 4-460 lever diverter, FS hand spray, 060 tub spout, 4-231 showerhead, 300 arm and flange.

Modifications: Suffix 3/4: 3/4" valve to increase flow approximately 20% • Suffix 72: 6' hose in place of 5' hose • Suffix QD: Quick-disconnect on hand spray units
 • Suffix R: White vinyl hose in lieu of metal hose • Suffix T: Toe tester in place of tub spout • Suffix VB: Elevated vacuum breaker with wall flanges in place of in-line vacuum breaker on hand spray units • Suffix X: Integral service stops - allows water shutoff at valve for service. Recommended for use on all multiple or commercial installations • Suffix X-CHK: Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve





1-100

Safetymix Shower Unit, 4-500 3-port valve, 4-231 showerhead, 300 arm and flange.
4-500 Valve only



1-215-X

Safetymix Tub/Shower Unit, 4-500X 4-port valve, 050 diverter spout, 4-231 showerhead, 300 arm and flange.



1-25-FSB

Safetymix Shower Unit with Open Flow Hand Shower, 4-500 3-port valve, FSB hand spray with 30° adjusting bar.



1-50-FSB

Safetymix Tub/Shower Unit with Open Flow Hand Shower, 4-500 3-port valve, 4-45B lever diverter, 060 tub spout, FSB hand shower, with 30° adjusting bar.



1-117-FS

Safetymix Shower Unit with Open Flow Hand Shower, 4-500 3-port valve, 4-45B lever diverter, FS hand shower, 4-231 showerhead, 300 arm and flange.



1-217-X-FS

Safetymix Tub/Shower Unit with Open Flow Hand Shower, 4-500 3-port valve, 4-460 lever diverter, 060 tub spout, FS hand shower, 4-231 showerhead, 300 arm and flange.

Modifications: Suffix X: Integral service stops - allows water shutoff at valve • Suffix BX: Back inlet and outlet connections, integral stops
• Suffix X-REV: Reverse coring, hot on right, cold on left, for back to back installations with integral stops only • Suffix 3/4: 3/4" valve to increase flow approximately 20% • Suffix L: Lucite handle in place of lever handle • Suffix FSB: Use in lieu of suffix FS is 30° adjusting bar is desired in place of wall hooks on hand shower units • Suffix B-4B: 4B" adjusting bar in place of 30° bar on hand shower units • Suffix VB: Elevated vacuum breaker in place of in-line vacuum breaker • Suffix QD: Quick disconnect on hand shower units • Suffix 6: 6' hose in place of 5' hose • Suffix R: Vinyl hose in place of metal on hand shower units • Suffix A: Anchor plates for valve and head • Suffix E: External volume control on head

