For Heating Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Series HWAHot Water Angle Valves

Sizes: 1/2" - 11/4" (15 - 32mm)


Features

- Threaded x male union or sweat x male union
- · Constructed of heavy duty bronze
- · Rising stem
- · Screwed-in bonnet
- Teflon® stem packing
- Bronze disc
- For use on gravity (hot water) heating systems only

Pressure - Temperature

Working Pressure Non-Shock Hot Water 60psi

Dimensions - Weights





Materials

Body: Bronze ASTM B584 C84400 Bonnet: Bronze ASTM B584 C84400 Stem: Brass ASTM B16 C36000

Disc: 1/2" - 3/4" (15 - 20mm) Brass ASTM B16 C36000

1" - 1¹/₄" (25 - 32mm) Rubber NBR

Disc Holder: Bronze ASTM B584 C84400

Packing Nut: Brass ASTM B16

Packing: Teflon® Handle: Plastic

Screw: Steel AISI 1020

Union Nut: Bronze ASTM B584 C84400

Tailpiece: Forged Brass ASTM B124 C37700

MODEL	SI	ZE (DN)	DIMENSIONS							WEIGHT		
			А		В		С		D			
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs	kgs.
TxTMU	1/2	15	23/8	60	27/8	73	1 ¹ / ₄	31	2 ⁵ / ₁₆	59	.73	.33
TxTMU	3/4	20	2 ⁷ / ₁₆	62	215/16	74	1 ¹ / ₈	29	2 ⁵ / ₁₆	59	.88	.40
<u>TxTMU</u>	1	25	2 ⁷ / ₈	72	35/8	92	1 ¹ / ₄	32	2 ⁵ / ₁₆	59	1.54	.70
TxTMU	1 ¹ / ₄	32	31/4	82	313/16	97	1 7/ ₁₆	36	2 ⁵ / ₁₆	59	2.12	.96
<u>CxTMU</u>	1/2	40	21/8	54	213/16	72	1	25	2 ⁵ / ₁₆	59	.68	.31
CxTMU	3/4	20	23/8	60	27/8	73	1 ¹ / ₄	31	2 ⁵ / ₁₆	59	.84	.38

Teflon® is a registered trademark of the E.I. Dupont de Nemours & Company, Incorporated.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



